



Bayonet resistance temperature probe with flattop

Techical Features			Type ZRK 100-01	
Resistance Temperature Probe	Resistance Temperature Probe		Norm	
	PT100		IEC 751	
	PT1000		IEC 751	
Comp.Cnt.	1 or 2			
Tolerance	Class B		DIN IEC 751	
	Class A		DIN IEC 751	
	Class 1/3B		DIN IEC 751	
	Class 1/10B		DIN IEC 751	
Temperature Range	-50~400° C (Standard)			
Sensor	Two wire			
	Three wire (Standard)			
	Four wire			
Insulation material	Heat conducting sealant/ MgO			
Sheath material	304 / 1.4301			
	Copper			
Sheath diameter	6.0mm 8.0mm			
	Other diameter on request			
Probe lenth	20mm			
Measuring inserts	20mm...175mm		Compression springs length	
Cable material	Silicone (Shield can be select,please specify)			
	PTFE / FEP (Shield can be select,please specify)			
Cable length	Metal braiding			
	Please specify			
Termination	Bare (Standard)			
	Ferrules			
	Receptacle			
	Miniature plug			
	Standard plug			
Bayonet Specification	Air plug			
	Inner diameter	12mm		
	Inner diameter	15mm		
	Inner diameter	16mm		
Accessories	Bayonet sockets			
	M10x1mm			
	G1/4			
	M14x1.5mm			
	G3/8			
	Other specification on request			

