


Mineral-insulated thermocouple with cable

TYPE: MTC 100		Technical features			
	thermocouple	thermocouple	plus	minus	norm
		Type K	NiCr	NiAl	IEC 584
		Type J	Fe	CuNi	IEC 584
		Type L	Fe	CuNi	DIN 43710
		Type T	Cu	CuNi	IEC 584
		Type N	NiCrSi	NiSi	IEC 584
		Type E	NiCr	CuNi	ICE 584
	sensor	1 or 2			
	tolerance	Class 1 DIN IEC 584			
	insulation material	MgO			
	sheath material	304 / 1.4301			
		316L / 1.4404			
		310S / 1.4845			
		inconel600			
		Nicromil ①			
	probe diameter	0.15 mm	0.5mm	1.0 mm	
		1.5 mm	2.0mm	3.0 mm	
		4.0 mm	5.0mm	6.0 mm	
		other diameter on request			
	bending radius	minimum 5 x the external diameter			
	probe length(A)	please specify			
	cable material	PVC			
		silicone			
		PTFE / FEP			
		metal braiding			
cable length(B)	glass fibre				
	shield can be select,please specify				
	please specify				
temination	bare (standard)				
	ferrules				
hot junction	receptacle				
	insulated (standard)				
accessories	uninsulated				
	cable protector: coil				
	Adjustable thread join (see attached list 1)				

① , Nicromil Highly resistant to general corrosion and stress-corrosion cracking.Can be operated up to 1250° C.