

拧入式导线带微型插头铠装热电阻

型号：MRC 210

The image is a technical drawing of a thermocouple probe. It consists of a long, thin cable with a threaded top section and a three-pin plug at the bottom. The top section is labeled 'A' and the cable section is labeled 'B'. A break symbol is shown in the middle of the cable. The plug has three pins labeled with symbols: a circle with a dot, a circle with a plus sign, and a circle with a minus sign.

技术参数

	铂电阻类型	标准
铂电阻	PT100	IEC 751
	PT1000	IEC 751
元件数量	1或2	
精度	Class B	DIN IEC 751
	Class A	DIN IEC 751
	Class 1/3B	DIN IEC 751
	Class 1/10B	DIN IEC 751
测温范围	-200~300° C	
	-50~400° C (标准)	
	-50~600° C	
	-200~600° C	
传感器	两线制	
	三线制 (标准)	
	四线制	
绝缘材料	MgO	
保护管材料	不锈钢 304 / 1.4301	
	不锈钢 316L / 1.4404	
	不锈钢 310S / 1.4845	
	inconel600	
保护管直径	1.5mm	2.0mm 3.0 mm
	4.0mm	5.0mm 6.0 mm
	其他直径可以定做	
保护管弯曲半径	5倍保护管的直径	
保护管长度	按需定做	
导线材质	PVC	
	硅胶	
	特佛龙 / PTFE / FEP	
	金属网	
	可选导线带屏蔽，请标注	
导线长度	按需定做	
螺纹规格	规格尺寸，按要求定做，详见附表1	
附件	防折弹簧	