

带标准插头直连式铠装热电电阻

型号：MRA 300

A technical drawing of the MRA 300 probe. It consists of a long, thin cylindrical probe body and a three-wire connector at the bottom. A dimension line labeled 'A' indicates the total length of the probe body. The connector has three pins and is marked with ⊕, ⊕, and ⊖.

技术参数

铂电阻	铂电阻类型	标准			
	PT100	IEC 751			
	PT1000	IEC 751			
元件数量	1或2				
精度	Class B	DIN IEC 751			
	Class A	DIN IEC 751			
	Class 1/3B	DIN IEC 751			
	Class 1/10B	DIN IEC 751			
测温范围	-200~300° C				
	-50~400° C (标准)				
	-50~600° C				
	-200~600° C				
传感器	两线制				
	三线制	(标准)			
	四线制				
绝缘材料	MgO				
保护管材料	不锈钢 304 / 1.4301				
	不锈钢 316L / 1.4404				
	不锈钢 310S / 1.4845				
	inconel600				
保护管直径	1.5mm	2.0mm	3.0 mm		
	4.0mm	5.0mm	6.0 mm		
	其他直径可以定做				
保护管弯曲半径	5倍保护管的直径				
保护管长度	按需定做				
附件	卡套螺纹(规格尺寸，按要求定做，详见附表1)				