

Quality products

ISOHEAT®

矿物绝缘加热线缆 Mineral-insulated heating cable



MiL-HC-SS/CN 系列 Series MiL-HC-SS/CN

表面温度可达 600° C

根据ATEX标准，该产品也可以用于防爆环境

for heating cable temperatures up to 600 °C
Also available in EX-version based on rules
of ATEX



激光焊接

Laser welded connexion

描述

成品矿物绝缘线缆具有不锈钢外壳（1.4541），加热温度可以达到800摄氏度。
具有高回弹性能，适用于高加热功率传导的需求，成型加热器，加热板等。

Description:

Finished assembled mineral insulated heating cable with metal sheath made up of stainless steel for heating cable temperatures to 600°C. This heating cable is preferred for pipe heat tracing and tank heating systems used in medium temperature range.

订购参数

Order data

50W/m

长度 lengths (m)	功率 power(W)	订货号 order-no.
25.7	1285	24000257
32	1600	24000320
41	2050	24000410
51	2550	24000510
65	3250	24000650
81	4050	24000810

其他长度，电压和功率可根据需求订购

Other lengths, voltages and powers available for delivery upon request

Order data

70W/m

长度 lengths (m)	功率 power(W)	订货号 order-no.
22	1540	24100220
27	1890	24100270
34.5	2415	24100345
43	3010	24100430
55	3850	24100550
68	4760	24100680