

Quality products

ISOHEAT®

管接头 MiL fittings overview



描述

我们提供的标准加热软管配有高铬钢配件。配件材料可选择不锈钢（1.4305或者1.4571不锈钢）或黄铜。请注意，根据胶管内径确定接头尺寸，管接头内径小于胶管内径。

Description:


Our heated hoses we deliver in standard with fitting in bichromated steel. As option all fittings available in stainless steel (1.4305 or 1.4571) or brass.

Dimension of fitting depending from inner diameter of core. Please note, that inner diameter of fitting is smaller than inner diameter of core.

胶管外径 diameter nominal DN	mm	4	6	8	10	12	16	20	25	32	40
管接头内径 inner diameter fitting	mm	3,0	4,5	6,0	7,5	10	12,5	16	20,1	27,5	31,5

DKR (DIN 3863)

universal conical nipple,
union nut inch (BSP)




标准宽度 nominal width DN (NW)	螺纹尺寸 thread Inches	SW
4	G 1/8"	15
4	G 1/4"	17
6	G 1/4"	17
6	G 3/8"	19
10	G 3/8"	19
10	G 1/2"	27
12	G 1/2"	27

标准宽度 nominal width DN (NW)	螺纹尺寸 thread inches	SW
16	G 1/2"	32
20	G 3/4"	32
20	G 1"	41
25	G 1"	41
25	G 1 1/4"	50
32	G 1 1/4"	50
40	G 1 1/2"	56

DKJ (DIN 3863)

nipple with 74°-conus JIC,
union nut UNF-thread




标准宽度 nominal width DN (NW)	螺纹规格 thread UNF	SW
6	7/16-20	14
6	7/2-20	17
6	9/16-16	17
8	1/2-20	17
8	9/16-18	17
10	3/4-16	24
12	3/4-16	24

标准宽度 nominal width DN (NW)	螺纹规格 thread UNF	SW
13	7/8-14	27
16	7/8-14	27
16	1 1/16-12	32
20	1 1/16-12	32
25	1 5/16-12	38
32	1 5/8-12	51
40	1 7/8-12	56

RSL

pipe connection light




标准宽度 nominal width DN (NW)	公称通径 pipe-Øa mm	长度 length mm
4	6	25
6	8	25
8	10	26
10	12	26
12	15	28

标准宽度 nominal width DN (NW)	公称通径 pipe-Øa mm	长度 length mm
16	18	32
20	22	32
25	28	34
32	35	41
40	42	41

76

RSS

pipe connection heavy




标准宽度 nominal width DN (NW)	公称通径 pipe-Øa mm	长度 length mm
4	8	27
6	10	29
8	12	29
10	14	33
12	16	33

标准宽度 nominal width DN (NW)	公称通径 pipe-Øa mm	长度 length mm
16	20	39
20	25	44
25	30	48
32	38	55

DKL (DIN 3863)

universal conical nipple,
union nut metric thread light

标准宽度 nominal width DN (NW)	公称通径 thread Inches	SW
4	M 12 x 1,5	17
6	M 14 x 1,5	17
8	M 16 x 1,5	19
10	M 18 x 1,5	22
12	M 22 x 1,5	27




标准宽度 nominal width DN (NW)	公称通径 thread inches	SW
16	M 26 x 1,5	32
20	M 30 x 2	36
25	M 36 x 2	41
32	M 45 x 2	50
40	M 52 x 2	60

DKM (DIN 3863)

universal conical nipple,
union nut metric thread

标准宽度 nominal width DN (NW)	公称通径 thread Inches	SW
20	M 30 x 1,5	36
25	M 38 x 1,5	46




标准宽度 nominal width DN (NW)	公称通径 thread Inches	SW
32	M 45 x 1,5	32
40	M 52 x 1,5	36

DKS (DIN 3863)

universal conical nipple,
union nut metric heavy

标准宽度 nominal width DN (NW)	公称通径 thread Inches	SW
6	M 18 x 1,5	22
8	M 20 x 1,5	22
10	M 22 x 1,5	27
12	M 24 x 1,5	30




标准宽度 nominal width DN (NW)	公称通径 thread Inches	SW
16	M 30 x 2	32
20	M 36 x 2	36
25	M 42 x 2	41
32	M 52 x 2	50

BDN

flanged nut flat packing,
union nut inch / BSP

标准宽度 nominal width DN (NW)	公称通径 thread Inches	SW
4	G 1/4"	17
6	G 1/4"	17
8	G 3/8"	19
10	G 3/8"	19
10	G 1/2"	27
12	G 1/2"	27
16	G 3/4"	32




标准宽度 nominal width DN (NW)	公称通径 thread Inches	SW
20	G 3/4"	32
20	G 1"	41
25	G 1"	41
25	G 1 1/4"	50
32	G 1 1/4"	50
40	G 1 1/2"	56

BDN

flanged nut flat packing,
union nut metric

标准宽度 nominal width DN (NW)	公称通径 thread Inches	SW
4	M 12 x 1,5	17
6	M 14 x 1,5	17
8	M 16 x 1,5	19
10	M 18 x 1,5	22
12	M 22 x 1,5	27



标准宽度 nominal width DN (NW)	公称通径 thread Inches	SW
16	M 26 x 1,5	32
20	M 30 x 2	36
25	M 36 x 2	41
32	M 45 x 2	50
40	M 52 x 2	60

加热软管也可以按照DIN或ASA的要求配置非固定或固定法兰，可以依据客户要求定制。

Heating hoses can be delivered also with loose or fix-flanges as DIN or ASA.
Special constructions available on request.